



- Z-Wave Plus
- Overload protection
- Support Roller Blinds, Curtain And Shutter
- Auto report the shutter states
- Act as Z-wave Repeater automatically
- Longer Z-wave Signal transmission
- AES 128 bit Z-wave encryption

Specification

| | |
|-------------------------------|-------------------------------------------------------------|
| Model | SA-103 |
| Z-Wave Standard | Z-wave plus |
| Z-Wave Frequency | CE : 868.40 MHz, 869.85 MHz FCC : 908.40 MHz, 916.00 MHz |
| Maximum transmission distance | 40 M |
| Power overload | 6 A |
| Supply Voltage | 90 ~ 240 VAC |
| Output Current | 5 A (Resistive Load) |
| Maximum Measurement Error | 3 W (Under 40 W) |
| Measurement Error Rate | 5% (Under 40 W) |
| LED Indicator | 1 Red LED |

Dimension and Environment

| | |
|-----------------------|------------------------------|
| Dimensions | 47.5(L) x 39(W) x 15.6(H) mm |
| Operating Temperature | 0 ~ 40° C |
| Storage Temperature | 85% RH max |

Standard Package

| | |
|-----------------|---------------------|
| Package Size | 15.5 * 6.2 * 2.8 cm |
| Package Weight | 0.55 kg |
| Package Content | SA-103 * 1 |

Carton Package

| | |
|------------|--------------|
| Quantity | 150 |
| Dimensions | 46 * 36 * 30 |
| Weight | 83.5 kg |